

# Specifications

Displacement	<b>9.9 cu in. (163 cc)</b>
Fuel Capacity	<b>0.82 gal (3.1 L)</b>
Oil Capacity	<b>0.61 qt (0.58 L)</b>
Clutch	<b>Spring-loaded belt tightener</b>
Honda Engine	<b>4-Cycle Honda GX160; recoil start; on/off switch; low-oil alert</b>
Drive	<b>• V-belt engine-to-gear case• Double roller chain-to-blade eccentric shaft• Gears and roller chain-to-traction wheels• Transmission has separate dog clutches to engage cutting blade and traction drive</b>
Drive Wheel	<b>(2) 8 in. (203 mm) diameter, knob tread; rubber-vulcanized to cast-iron hubs</b>
Lubrication	<b>Oil splash in gear case; grease fittings elsewhere</b>
Speed	<b>Up to 135 ft/min (41 m/min)</b>
Cutting Width	<b>18 in. (457 mm)</b>
Cutting Thickness	<b>Adjustable up to 2.5 in. (64 mm)</b>
Width	<b>25 in. (635 mm)</b>
Length	<b>53 in. (1,346 mm)</b>
Height	<b>40 in. (1,016 mm)</b>
Tires	<b>Rear: 9" x 3.50"-4 with sealed ball bearings</b>